

LIFESPANTM

COMPOSITE ARCHITECTURAL BEAMS

Installation points

Standards

Legislation may differ between jurisdictions. Before installing any Eva-Last product, ensure that the application is rational and complies with the local regulations and building codes. Wherever necessary, consult a suitably qualified professional. Be sure to comply with material manufacturer specifications. Where manufacturers and building codes differ, revert to the building code requirements. Check that your choice of product is suitable for its intended application. For further product specification and information visit www.eva-last.com

Safety

- Always wear appropriate personal protection equipment (PPE). Comply with the local occupational health and safety legislation.
- Refer to the applicable Material Safety Data Sheet (MSDS).
- Cutting LifeSpan produces fine particulate matter.
 - Work in well-ventilated areas.
 - Wear dust masks during cutting, drilling and cleaning.
 - Clean up saw-dust by vacuuming or wetting the area down and sweeping.
 - Always wear safety goggles while cutting and installation.
 - Saw dust may be slippery.
 - Cut beams may have sharp edges (particularly mitred cuts).
 - Wear gloves when working with beams.

Storage and handling

- Individual beams are lighter than WPC and can be more easily handled. Beams are, however, bundled for convenience and can, as a result, be heavy. Take care when lifting, placing or removing from raised pallets.
- More than one person may be required for lifting. This is dependent on the length of the beams and the number of beams within a bundle.
- Ensure the mass handled does not exceed safe limits as defined by applicable local legislation.
- When handling lengths of beams higher than 4 m, ensure both ends are lifted simultaneously and evenly. Lift the beams 1 m from each end to provide better control.
- Handle the beams carefully. Dropping the beams (and all high impact loads in general) can result in damage to the profiles.
- During transportation use corner protectors where strapping is required.
- All components should be stored completely undercover.
- When storing beams, a pallet or flat surface should be used to support the full length of each component.
- All components should be securely stored.
- No component should sit in water or similar.
- Avoid over-stacking and eccentric stacking.
- Don't stack the beams vertically.

Plan

- Assess the site environment and ensure the product is suitable for the intended application.
- Classify the corrosion category, loading class, and any other property that will influence the selection of product.
- Determine appropriate spans for the selected profile. This will depend on the application and the loading class for the region. Suggested spans are provided for typical residential scenarios (refer to Installation guide).
- An appropriately qualified professional must be consulted whenever necessary to ensure the product, this document and the intended application complies with all applicable legislation for that region.
- Develop a maintenance plan to ensure the longevity of the system. This should consider drainage, corrosion and vegetation.

Site preparation

- Ensure adequate drainage. Prevent pooling water and/or erosion.
- Consider light conditions before installing beams and features near windows and entry ways.


Cutting

- Use a sharp, fine-toothed, carbide-tipped blade designed for Aluminum to cut LifeSpan material.
 - Use a non-ferrous-aluminum-cutting chip saw blades with a maximum of two teeth per centimeter.
 - Do not use grinders or chainsaws for cutting.
 - Using an inappropriate blade may result in peeling or deformations in the beam.
- LifeSpanTM beams are provided as factory cut. Ends should be trimmed to carpentry cut.
- Beams can be mitred.
- Don't router LifeSpan beams.
- Don't use oil to lubricate or cool blades as this may stain the product.
- Don't allow the blade to exceed 60 °C when cutting the beams.
- Support both ends of the beams when cutting.

Fastening

General

- Consult local building codes for span requirements and fastener sizes.
 - Check strength requirements before fastening joints as additional reinforcement may be required.
- Do not use nails.
- Avoid using threaded fasteners, tapping or pre-drilling screws when fastening into thin aluminum structures without fastener reinforcing points within the profile.
- Glues may stain the cap of the beam. This can be sanded off but may create an inconsistent finish.
- When fastening, attempt to fasten through the internal walls of the profile and not just the external walls.
- Do not over-tighten fasteners as this may cause profiles to crack or cause other deformations.
- Generic truss and purlin brackets can be used to support beams.
- When considering fasteners and brackets, attention should be paid to dissimilar materials that may cause accelerated corrosion in the right environments.
- Beams can be joined and supported by metal inserts within the cavity of the beams. These must be painted and treated for environmental conditions.




Drilling

- Owing to the ductility (softness) of the aluminum material, additional care should be taken when drilling.
 - Use a sharp cut drill bit, designed to drill through aluminum with a tip angle of 130° - 140° to avoid chipping or burring.
 - Use a carbide or hardened drill bit to maintain the sharp edge.
- Allow the drill bit to do the work; do not apply force to the drill as this may cause deformation in the beam.
- To avoid material burring out from the back of the beam, drill through a single face and then turn the beam to drill through the next.
 - A sacrificial beams can be used to provide support while drilling through the back of a face.

Fastener types

1. Bolts


- Bolts should be specified in accordance with structural requirements.
- Dome nuts and bolts can be used for a better aesthetic.
- Always use rubber or plastic washers.



Bolts (structural fastening)

2. Rivets and threaded blind rivets

- Use only for non-structural applications or when a beam is properly supported by a structural element, such as a truss clip.
- Blind rivets allow for threaded fasteners to be used while providing structural stability to the fastener.



Blind rivets (non structural fastening)

Glues

Use to fasten non-structural elements to beams. Glues specifically designed for securing plastic to aluminum connection can be used, such as:

- Multipurpose; high bonding strength adhesives, such as Sikaflex Crystal Clear.
- Structural adhesives, such as Scotch Weld DP-8010.

Maintenance

- Remove all post-installation burrs and marks by sanding.
- Use soap and water to remove dirt.
- Profiles can be gently sanded to remove stains.
- Sand along the grain of the beams for best results.
- Deep scratches can be mended by melting composite saw dust into the scratch and then smoothing it down.

Disclaimer & copyright

Disclaimer

The provided information is offered in good faith as accurate but without guarantee. Eva-Last makes no warranties or representations of any kind (express or implied) about the accuracy, adequacy, currency, or completeness of the information, or that it is necessarily suitable for the intended use.

Compliance with this document does not guarantee immunity from breach of any statutory requirements, building codes or relevant standards. The final responsibility for the correct design and specification rests with the designer and, for its satisfactory execution, with the contractor. Appropriate warnings and safe handling procedures should be provided to handlers and users.

While most data have been compiled from research, case histories, experience and testing, small changes in the environment can produce marked differences in performance. The decision to use a material, and in what manner, is made at your own risk. The use of a material and method may therefore need to be modified to its intended end use and environment.

Eva-Last, its directors, officers or employees shall not be responsible for any direct, indirect, or special loss or damage arising from, or as a consequence of, use of, or reliance upon, any information contained in this document or other documents referenced herein. Eva-Last expressly disclaims any liability which is based on or arises out of, the information or any errors, omissions, or misstatements herein.

Drawing disclaimer

All dimensions and specifications are offered in good faith as accurate but without guarantee. The information captured herein may not contain complete details. Eva-Last makes no warranties or representations of any kind (express or implied) about the accuracy, adequacy, currency, or completeness of the information, or that it is necessarily suitable for the intended use.

Compliance with this document does not guarantee immunity from breach of any statutory requirements, building codes or relevant standards. The final responsibility for the correct design and specification rests with the designer and, for its satisfactory execution, with the contractor.

Utilisation disclaimer

Legislation may differ between jurisdictions. Before installing any Eva-Last product, ensure that the application is rational and complies with the local regulations and building codes. Wherever necessary, consult a suitably qualified professional. Be sure to comply with material manufacturer specifications. Where manufacturers and building codes differ, revert to the building code requirements. Check that your choice of product is suitable for its intended application. For further product specification and information visit www.eva-last.com.

Copyright

If reprinted or reproduced or utilised in any form Eva-last should be acknowledged as the source of the information. Eva-last periodically updates the information contained in this installation guide and that of the Eva-last documents that have been referenced herein. Before using this installation guide, please refer to the Eva-last website (www.eva-last.com) for the most recent updates on information contained in this installation guide and that of any referenced Eva-last documents. Please refer to the applicable websites for the most recent updates on information contained herein pertaining to other sources.

Contact information

Eva-Last
Room 1203, 12/F Tower 333 Canton Road,
Tsimshatsui, Hong Kong, China

Emergency Contact: +27 10 593 9220
Product information: +27 10 593 9220
Email: info@eva-last.com
Website: www.eva-last.com